# **Multifunction table clamps**



Table clamping elements

Secure your workpieces for precision routing, sanding, drilling and cutting on 20 mm tables with BESSEY®'s new Horizontal table clamp fixture.

Use the WNS20-MFT-SET for precise and fast machining of work pieces. The patented pull-down mechanism ensures the workpiece does not lift from the surface during clamping and lies flat on the surface. Make quick adjustments with the side clamping lever as the rubber pads grip any shape in place.

### Patented Low profile design

The patented pull-down mechanism prevents the work piece from lifting off the table – no fastening screws are required.

### Secure work pieces

Hold work pieces on a 20 mm hole grid system. For use on multifunction tables such as Festool MFT and Sortimo WorkMo.

### **B** Quick clamping

Apply up to 165 lbs of clamping pressure using the side clamping lever

### Hold odd shaped work pieces

Round and flat work pieces are easy to position and hold thanks to camaction side lever and rubber pads that enable easy locking and quick release for a secure grip





## Horizontal table clamp fixture, WNS20-MFT-SET

BESSEY's new horizontal clamp fixture can be used on multifunction tables with a hole diameter of 20 mm with a plate thickness minimum of 19 mm. Cam-action levers and rubber-padded clamp surfaces enable easy locking and quick release for a secure grip on your material, regardless of shape. Includes, 2 x horizontal pull-down clamps, 2 x bench dogs and 4 x knurled nuts.

	Table	Workbench	Clamping	Approx.
	Thickness	Hole Diameter	Pressure	Weight
WNS20-MFT-SET	19 mm (≥)	20 mm	170 lbs	1.78 lbs



# Table bench dog assembly 4 x bench dogs and 4 x knurled nuts for 20 mm work tables like Festool MFT and Sortimo WorkMo.

BH20-MFT-SET







# **Multifunction table clamps**

Table clamping elements





## Table clamp with ratcheting lever, KLI20-MFT-SET

Based on the popular KliKlamp style, the new, ratcheting lever clamp combines quality and functionality for fast, easy and safe clamping on 20 mm tables (Festool MFT, Sortimo WorkMo). The KLI20-MFT-SET features a multi-stage ratchet mechanism (with quick release button) that allows up to 150 lbs clamping force to be achieved very guickly with little effort. The KLI20-MFT-SET has a lightweight magnesium sliding arm for rapid, vibration-free clamping. Offered as a 2-piece set.

	Table Thickness	Workbench Hole Diameter	Opening	Throat Depth	Clamping Pressure	Approx. Weight
KLI20-MFT-SET	19 mm (≥)	20 mm	6" (150 mm)	3" (80 mm)	150 lbs	1.37 lbs

## Accessory for use on multifunction (MFT) tables

Works with matrix tables having 20 mm diameter holes (e.g. Festool MFT). Ideal for work surfaces 19 to 25 mm thick. Set includes: 1X cylindrical screw M8 x 35 mm; 1X lock pin 20 mm OD x 17 mm long; 1X knurled knob with M8 thread.

Use on BESSEY Auto Adjust toggle clamps with horizontal base plate: Horizontal toggle clamp STC-HH50 / -HH70; Push/pull clamp STC-IHH25; Vertical toggle clamp STC-VH50

STC-SET-T20 is a low cost optional accessory - clamps not included.

	Clamp Hole Diameter	Workbench Hole Diameter
STC-SET-T20	8.2 mm	20 mm

Approx. Weight 0.21 lbs

# Track/table clamp, GTR

High clamping force for safety. Ergonomically shaped wooden handle.

	Clamping Capacity	Throat Depth	Clamping Force	Approx. Weight
GTR12	<b>4</b> <sup>1</sup> / <sub>16</sub> "	<b>2</b> 5⁄16"	400 lbs	0.66 lbs
GTR16B6	<b>6</b> <sup>5</sup> / <sub>16</sub> "	<b>2</b> <sup>5</sup> ⁄16"	400 lbs	0.71 lbs
GTR30B6	<b>11</b> <sup>13</sup> / <sub>16</sub> "	<b>2</b> <sup>5</sup> ⁄16"	400 lbs	0.90 lbs

## Track/table clamp, GTRH

Clamping force is variable, with ratchet action lever up to 5 times faster than conventional clamps. Secure - lever / ratchet unaffected by vibrations. Strong - clamping force up to 540 lbs nominal clamping force.

	Clamping	Throat	Nominal Clamping	Approx.
	Capacity	Depth	Force	Weight
GTR16S6H	<b>6</b> <sup>5</sup> / <sub>16</sub> "	<b>2</b> 5⁄16"	540 lbs	1.17 lbs

**BESSEY®** Tools North America 1-800-828-1004 · Fax (519) 621-3442





besseytools.com



