

GearKlamp



BESSEY is introducing a first of its kind in the world with the GearKlamp GK: The clamp that conveniently masters clamping applications in a perfect way – even in the tightest spaces. For example, the compact BESSEY GearKlamp GK can be skill used even in places that were previously difficult or impossible for clamping tools to access.

Unique compact design

The GearKlamp is extremely flexible and can even be used in the tightest of spatial conditions:

- due to the patented mechanism that separates the handle from the spindle and positions it around the rail
- due to the crossed v-grooves on the upper section for securely holding round, pointed and angular components



Robust technology

Meeting the BESSEY quality promise was a focus in development, and so the transmission clamp is also a winning choice in terms of durability:

- due to the use of high-quality materials, such as fibreglass-reinforced polyamide for the top and bottom, as well as hardened, tempered and burnished steel for the profiled rails
- due to the sliding bar's plastic housing, the driving mechanism is protected from dust and splintering

Ergonomic use

The clamp contains all kinds of clamping technology and guarantees the user greater comfort:

- due to the high-quality two-component plastic handle for safe handling
- due to the quick-release shift button for quickly adjusting the sliding bar
- due to the swivelling pressure plate for exact alignment of the workpiece



Clamping in a narrow section can cause problems when using classic screw clamps and lever clamps as the handle prevents the clamp from being placed correctly.



The risk of damage to the workpiece and injury increases in confined working areas when clamping tools with protruding components are used.



The clamping in front of a closed surface is not possible due to the positioning of the handle with classic screw clamps and lever clamps as the handle cannot be actuated.

The new GearKlamp GK from BESSEY makes it conveniently possible – without additional aids, with enhanced ergonomics, with reduced risk of damage or injury



GearKlamp GK



Order number	Opening	Throat depth	Rail	Weight	PU	V3
	mm	mm	mm	kg	qty.	
GK15	150	60	19 x 6	0.62	6	
GK30	300	60	19 x 6	0.73	6	
GK45	450	60	19 x 6	0.84	6	
GK60	600	60	19 x 6	0.94	6	



- High-quality two-component plastic handle positioned around the rail, so clamp can be used in tight spaces
- Clamping force up to 2,000 N
- Easy-to-move trapezoidal thread spindle with swivelling pressure plate
- Quick-release shift button to quickly adjust sliding bar

BESSEY Tool GmbH & Co. KG ■ Mühlwiesenstraße 40
74321 Bietigheim-Bissingen, Germany
Fon +49 7142 401-0 ■ Fax +49 7142 401-452
E-Mail: tool-info@bessey.de

More information
www.bessey.de



Your dealer: