

Mobiele lijmpersen



Deurenspanner TB / TL



Bestelnummer	Spanwijdte		Bekafmetingen b x h	Gewicht	VE	V3
	mm	"				
met T-profiel 40 x 40 x 5 mm						
TB100	1000		66 x 43	5,07	1	
TB120	1200		66 x 43	5,54	1	
TB150	1500		66 x 43	6,03	1	
TB210	2100		66 x 43	7,87	1	
TB250	2500		66 x 43	9,43	1	
licht met I-profiel 37 x 11 x 4,5 mm						
TL60	600		48 x 53	3,78	2	
TL90	900		48 x 53	4,80	2	
TL120	1200		48 x 53	5,06	2	
TL180	1800		48 x 53	7,10	2	



TB:

- Max. spankracht 14.000 N
- Met vast gemonteerde vergrendelingsbout
- Knevelgreep
- Stabiel dankzij T-profiel

TL:

- Max. spankracht 9.900 N
- Eenvoudig verstelbare drukkoppen
- Hendel
- Stabiel dankzij I-profiel

Buis-schroeflijmtang BPC



Bestelnummer	voor buis Ø		Spandiepte	Gewicht	VE	V3
	mm	"				
BPC-H12	21,3	½	40	0,88	4	
BPC-H34	26,9	¾	42	1,23	4	



- Passend voor stalen buis DN 20 / R 3/4" resp. DN 15 / R 1/2"
- Buiten-diameter 26,9 mm resp. 21,3 mm
- Spanwijdte vrij te kiezen
- Met voet